



BEARING-SINGAPORE (PTE)LTD.



30 mm x 62 mm x 16 mm NTN 7206CG/GNP4
angular contact ball bearings

Bearing No. 7206CG/GNP4

7206CG/GNP4 Bearing 2D drawings and 3D CAD
models

Size	30x62x16 mm
Bore Diameter	30 mm
Outer Diameter	62 mm
Width	16 mm
d	30 mm
D	62 mm
B	16 mm
C	16 mm
Angle (°)	15 °
Category	Precision Ball Bearings
Inventory	8.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.191
EAN	4547359439533
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material - Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	15 Degree
Preload	Light
Raceway Style	1 Rib Outer Ring
Cage Material	Nylon
Rolling Element	Ball Bearing



BEARING-SINGAPORE (PTE)LTD.

Mounting Arrangement	Universal
Flush Ground	Yes
Inch - Metric	Metric
Other Features	Single Row Angular Contact
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearings; 15 Degree Contact Angle; Nylon Cage Material; 1 Rib Outer Ring Racewa
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	7206CG/GNP4
Weight / LBS	0.421
Outside Diameter	2.441 Inch 62 Millimeter
Bore	1.181 Inch 30 Millimeter
Width	0.63 Inch 16 Millimeter
bore diameter:	30 mm
radial static load capacity:	14700 N
outside diameter:	62 mm
operating temperature range:	-40 to 120 ° C
overall width:	16 mm
cage material:	Nylon
contact angle:	15 °
outer ring width:	16 mm
row type & fill slot:	Single-Row Non-Fill Slot



BEARING-SINGAPORE (PTE)LTD.

maximum rpm:	24500 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 4
closure type:	Open
fillet radius:	1 mm
snap ring included:	Without Snap Ring
series:	72C
bearing material:	High Carbon Chrome Steel
weight:	0.191 kg
radial dynamic load capacity:	23000 N
manufacturer product page:	Click here